Product data sheet

AVENIDA LENS LED 25W 3200LM 4000K IP66 018 - FOR PEDESTRIAN ZONES GRAY II 130272.5L052.011

LUG










Park luminaire in modern form for LED light sources. Mounting: on pillar ø48/60/76mm, with mounting bracket (included) Body: high pressure die-cast aluminum Lateral Surface Wind Exposed: 0,088 m² Power: 220-240V 50/60Hz Lifetime (L90B10); 100 000 h Available on request: DALI, LLOC, twilight sensor, 10kV surge protection, NTC Other remarks: the pole is not part of the luminaire Warranty: 5 years Application: cycle paths, avenues, sidewalks, parks, residential, public spaces, playgrounds, promenade, residential area roads Type of optics: 018 - for pedestrian zones

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	25 W	CRI	70
Total flux	3200 lm	LOR	100%
Luminous efficacy	128 lm/W	ULOR	2%
		Total power	25 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 14.17 in Width: 14.17 in Height: 18.98 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 25 W Appliance Class: II

Protection

IP: 66 IK: 10