Product data sheet

RAX SOFT 150 SATIN ASYMMETRIC 3000LM 4000K RA>80 TRAILING EDGE DIMMING
7021982125423
SG ARMATUREN

IP 20 IK 08

Rax Soft 150 in an asymmetric version for illuminating walls in corridors, offices etc. The asymmetric lens gives excellent light control and provides a conical light pattern on the wall, minimizing glare and giving a comfortable wall illumination. Rax Soft 150 Asymmetric is installed easily with springs that fit ceiling panels with a thickness of 1–50 mm. Light distribution Direct Light technic LED 30W 4000K Ra>80 SDCM 2 L90/B10 >100,000 hrs Optic Satin Matt Reflector Control/Dimming Trailing edge dimming Protection Class II SELV IP20 IK08 Energy and approvals CE Materials and finish Housing: Flame retardant polycarbonate Colour: Satin matt Optics: PMMA Polymethylmethacrylat Mounting/Connection Recessed (downlight), Indoor Cable 3x0,75mm² Quick connector Max. luminaires per circuit breaker: B10: 25, B16: 41, C10: 40, C16: 65

Light output 1



1 x LED

Nominal lamp power	30 W	LOR	100%
Lamp flux	3000 lm	Total flux	3000 lm
Luminous efficacy	100 lm/W	Total power	30 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 6.54 in
Width: 6.54 in
Height: 3.27 in

Adjustability

Fixed

Electric

System power: 30 W
Appliance Class: II

Protection

IP: 20
IK: 08