


Product data sheet

ATLANTIC LED LT O HB CG-S
40071354869
EATON EMERGENCY LIGHTING




• LED safety luminaire with high protection class (IP65) for indoor and outdoor use • Specialized electronics with components for reliable operation down to -40 °C • Luminaire with limited surface temperatures for use in operating areas with fire hazard • Acc. HACCP suitable for use in food processing industry • Robust construction from aluminium diecast and high impact resistant cover made of polycarbonate • Numerous knock-outs for cable entries • Suitable for mounting heights up to 28 m by narrow beam optics and exceptionally efficient High Power LEDs • Up to 14 m from luminaire to luminaire with optics for open area illumination. • Minimum service requirement due to high service life of the LEDs (up to 50,000 hours) Service life is increased at -20°C ambient temperature • Shortened inspection effort due to CEWA GUARD technology • Automatic function monitoring of up to 20 luminaires per circuit • Reduced installation cost by STAR technology • Freely programmable mixed operation of the switching modes per luminaire in one circuit • Increased safety through SLI-technology, monitoring of up to 8 individual LEDs in series connection

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	4.7 W	CRI	80
Total flux	340 lm	LOR	100%
Luminous efficacy	72 lm/W	Total power	4.7 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	4.7 W	CRI	80
Total flux	340 lm	LOR	100%
Luminous efficacy	72 lm/W	Total power	4.7 W

Mounting mode
Ceiling mounted

Electric
System power: 9.4 W
Appliance Class: I

Shape and measurements

Length: 11.93 in

Width: 5.35 in

Height: 2.44 in

Adjustability

Fixed

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Protection

IP: 65

IK: 10