


Product data sheet

FLAT SLIM
312133.004.1.191
RZB



IP
65

IK
03

Series: Flat Slim Type of Protection: IP 65 Protection Class: I Voltage: 220 - 230 V / 50 - 60 Hz Slave luminaire (SL), bracket powder-coated diecast aluminium, cover secured by bayonet connection, cover glass opal , satin finish. Available Colours: silver, metallic Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 300, H 63 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 4000K Socket 1: Stecker Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 1600lm System power: 21W Beam Angle: 128° Number of fittings B10A: 77 Number of fittings B16A: 124 Number of fittings C10A: 77 Number of fittings C16A: 124 Inrush current: 0,22A Unified Glare Ratio: 21,1 EEC: A+ - A+A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	21 W	CRI	80
Total flux	1600 lm	LOR	100%
Luminous efficacy	76 lm/W	ULOR	14%
		Total power	21 W

Mounting mode

Wall mounted

Electric

System power: 21 W

Shape and measurements

Height: 2.48 in
Diameter: 11.81 in

Protection

IP: 65
IK: 03

Adjustability

Fixed