


Product data sheet

MODULE_50_VENUS_2_3W_LENS_NEUTRAL_WIDE
80635303_
PETRIDIS



- Lens: Spot, Medium, Wide. - 3W power consumption driven at 350mA. - 6W power consumption driven at 700mA. - Die cast aluminum heatsink anodized. - Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10). - Connection for operation with Constant Current. - CRI: min. 80 / SDCM: 3 - Luminus Efficacy: 3W: 4000 K: 164 Lm/Watt 3W: 3000 K: 154 Lm/Watt 6W: 4000 K: 152 Lm/Watt 6W: 3000 K: 142 Lm/Watt Upon request: - Available with highest colour rendering index (CRI) - Available at IP44 version.

Light output 1



1 x LED			
Nominal lamp power	3 W	LOR	76%
Lamp flux	444 lm	Total flux	337 lm
Luminous efficacy	148 lm/W	Total power	3 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 2.95 in

Diameter: 1.97 in

Adjustability

Fixed

Design

Material impression: Aluminum

Electric

System power: 3 W

Controller: Dimmable 1..10V, DALI

Appliance Class: III

Protection

IP: 40

Designation labels: CE