


Product data sheet

PRAGUE 2 BOLLARDS
PRA-10011-T3-8040
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 2700K 3000K , 4000K - Die-cast aluminium housing, frame and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - High-efficiency PMMA lens - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13.5 W	CRI	80
Total flux	1434 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	13.5 W

Mounting mode

Standing / Bollard

Shape and measurements

Length: 6.89 in

Width: 7.87 in

Height: 19.69 in

Weight: 5.7 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Electric

System power: 13.5 W

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 65

IK: 10

Surface temperature: 40°C