


Product data sheet

FT ESCAPE 300LM AT MNM TEL, 1-3H, IP (SET TO 3 H OPERATION)
FT2SE300ATT13IP
EATON EMERGENCY LIGHTING




- LED self-contained luminaire with Automatic Test (AT) for reduced inspection effort
- Safety luminaire, light distribution optimized for escape route application
- Non obtrusive design and slim housing (31.2 mm)
- Good lighting performance and spacing in a compact housing
- Possibility to modify the light distribution by changing the optical lens (option)
- Same aesthetic in IP43 and IP65 versions
- Selectable operating time (1/1,5/2/3h operation)
- Selectable operation mode (M or NM) via jumper
- Large working space, cable entries in flexible material and spirit level for easy and fast installation
- Transparent base plate with honeycomb footprint for easy replacement of existing products (IP4x use only)
- Low eco footprint thanks to eco designed luminaire, low consumption and Lithium battery
- Simple fault analysis and status display via bicolor LED
- Complete range of accessories (Recess Kit for Ceiling, Recessed Box for plaster and brick wall, Wire Guard)
- Other colours available on demand

Light output 1 (integrated)



Lamp type	LED	CCT	6500 K
Nominal lamp power	2 W	CRI	80
Total flux	100 lm	LOR	100%
Luminous efficacy	50 lm/W	ULOR	2%
		Total power	2 W

Light output 2 (integrated, emergency)



Lamp type	LED	CCT	6500 K
Nominal lamp power	2 W	CRI	80
Total flux	300 lm	LOR	100%
Luminous efficacy	150 lm/W	ULOR	2%
		Total power	2 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 9.06 in
Width: 4.72 in
Height: 0.79 in

Electric

System power: 4 W
Appliance Class: II

Adjustability

Fixed

Information regarding emergency functions

Supplementary emergency lighting

Emergency power supply: Single battery 1 h, Single battery 1.5 h, Single battery 2 h, Single battery 3 h

Emergency sign: N/A

Protection

IP: 65

IK: 02