Product data sheet

LUCAS IV (WALL FITTING) 9.834.3046.15

LEIPZIGER LEUCHTEN









Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp		
Nominal lamp power	50 W	
Lamp flux	2000 lm	
Luminous efficacy	28 lm/W	
CCT	3400 K	
CRI	54	

LOR	84%
Total flux	1675 lm
Total power	59 W



ı x High pressure merci	ıry vapour ıamp
Nominal lamp power	80 W
Lamp flux	4000 lm
Luminous efficacy	38 lm/W
CCT	3400 K
CRI	54

LOR 84%
Total flux 3351 lm
Total power 89 W

Mounting mode

Wall mounted

Shape and measurements

Height: 22.44 in Diameter: 22.44 in Electric

System power: 59-89 W

Protection

IP: 55