Product data sheet

LIGHTING FOR SPORTS FACILITIES

V1-P0-703X5-04D50-65K1257 AIRQUB SPORT TV 1120 W 1 120W 5700K TRANSPARENT DALI ASYMMETRIC AS1


VARTON



IP 67 IK 01

High-power floodlight with a wide range of wattage and optics. Best lumens/mass/size ratio in its class of solutions. Material: Cast aluminum radiator, steel body parts, acrylic optic.LEDs with a high color rendering index, for objects with hight requirements for television broadcasting. Installation: Surface-mounted using an adjustable bracket. The mounting bracket has an angle of inclination 30° to the horizontal for comfortable aiming of the spotlight.Angle of rotation: 30° to 165° in 5° increment. Application: Outdoor areas. Industrial facilities. Sports lighting. Input voltage (AC, 50Hz), V: 90...305 AC frequency, Hz: 50 Input voltage (DC), V: 127...250 Flicker, %: 1 Climatic modification and category of placement: УХЛ1 Protection class: I Ingress protection (IP): IP67 Impact resistance: IK01 Power factor: 0,95 https://www.varton.ru/products/sportivnoe-osveshchenie/airqub-sport-tv/airqub-sport-tv-1120-vt/svetodiodnyy-prozhektor-varton-airqub-sport-tv-1120-vt-5700-k-as1-dali/

Light output 1



1 x LED

Nominal lamp power	1120 W	LOR	100%
Lamp flux	124300 lm	Total flux	124301 lm
Luminous efficacy	111 lm/W	Total power	1120 W
CCT	5700 K		
CRI	90		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 26.61 in
Width: 22.83 in
Height: 28.39 in

Adjustability

Fixed

Electric

System power: 1120 W

Protection

IP: 67
IK: 01