

Product data sheet

ROUNDED MIDI

672313.004

RZB




IP
66

IK
08

Item Number: 672313.004 Series: Rounded Midi Type of Protection: IP 66 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Base and housing made of corrosion-resistant die-cast aluminium for outdoor use, powder coated. Diffuser spherical cap made of opal glass, satin finish. With fixing device. Screwless installation of the cover by means of bayonet mount with latch. Installation outside the sealed area with compensation for drill hole tolerance. Fitted as standard with diaphragm valve to prevent condensation. Lamp(mains voltage LED module) included. Available Colours: silver, metallic Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 268, , H 91mm Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Emergency Lighting System: standard Safety Marks: D-mark, F-mark Impact Protection: IK08 (5 Joule) Luminaire flux LED: 460lm System power: 7,4W Beam Angle: 117° Number of fittings B10A: 27 Number of fittings B16A: 17 Number of fittings C10A: 45 Number of fittings C16A: 28 Inrush current: 27A Unified Glare Ratio: 20,5 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	7.4 W	CRI	80
Total flux	300 lm	LOR	100%
Luminous efficacy	41 lm/W	ULOR	4%
		Total power	7.4 W

Mounting mode

Wall mounted

Shape and measurements

Height: 3.54 in

Diameter: 10.55 in

Adjustability

Fixed

Electric

System power: 7.4 W

Protection

IP: 66

IK: 08