


Product data sheet

MUNKEGAARD Ø460, OPALGLASS, LED 30W / 3000K
5742580304
LOUIS POULSEN



Munkegaard Design : Arne Jacobsen Concept : The fixture emits diffuse and comfortable light directed downwards. The white opal glass disc provides an even illumination of the surface. The glass disc appears to hover below the ceiling, due to its suspended placement, allowing light to slip out through the gap between the disc and the fixture. This results in a different visual experience. Finish : High lustre chrome plated or satin chrome-plated. White opal glass. Material : Diffuser: White opal glass. Trim ring: Stainless steel. Mounting : Ceiling thickness: Ø265mm: 1-50mm Ø450/525mm: 1-55mm. Ceiling cut-out: Ø265: 245 mm, Ø460: 440mm, Ø525: 505mm Class : Ingress protection IP20. Electric shock protection I w. ground. Weight : Max. 4.1kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	30 W	CRI	80
Total flux	2271 lm	LOR	100%
Luminous efficacy	76 lm/W	Total power	30 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.98 in
Diameter: 18.11 in

Adjustability

Fixed

Electric

System power: 30 W
Appliance Class: I

Protection

IP: 20