


# Product data sheet

ELSA-2 DL 68 OP 100° 500 830 WH  
E010298967  
ESYLUX



LED downlight, 5W for ceiling mounting Control system: ON/OFF Installation type: Recessed mounting Installation position: Ceiling  
Dimensions: Height/Depth 45 mm, Ø 98 mm Weight: 194 g Protection type: IP20 ApplianceClass: Class II Permissible ambient temperature: - 20 °C...+40 °C Colour: white, similar to RAL 9003 Nominal voltage: 220 - 240 V AC / 50 - 60 Hz TotalSystemPower: 6,5 W Luminous flux: 500 lm Luminous efficacy: 76 lm/W Colour temperature: 3000 K Colour rendering index R<sub>a</sub>: > 80 Rated lifetime L<sub>80</sub>>B<sub>50</sub> at 25 °C: 40000 h<p>ArticleNumber: E010298967 <https://www.esylux.com/p/E010298967>

## Light output 1



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| 1 x LED            |         |             |        |
| Nominal lamp power | 6.5 W   | LOR         | 100%   |
| Lamp flux          | 500 lm  | Total flux  | 500 lm |
| Luminous efficacy  | 77 lm/W | Total power | 6.5 W  |
| CCT                | 3000 K  |             |        |
| CRI                | 81      |             |        |

## Mounting mode

Ceiling recessed

## Shape and measurements

Height: 1.77 in  
Diameter: 3.86 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 6.5 W  
Ballast: ECG  
Appliance Class: II

## Protection

IP: 20  
Designation labels: CE

## Other operating numbers

Ambient temperature range: -4...104°F