Product data sheet

MRZ-4 MULTI-HEAD RECESSED INTEGRAL LED MRZ-1-REC-X-1H-L27-80-NFL-UNV-X-STD-SFL COOPER LIGHTING








Family of 1, 2, 3, or 4-head fixtures, Lumen packages from 250 to 1700+ per head in 80+ or 97+ CRI, +110 LPW, 25°, 40°, 55° optics; each head has 45° tilt with 365° degree rotation, Black housing & white trim/white housing & trim/black housing & trim, IC-rated fixtures with flanged and mud-in trims, 0-10V std dimming. Optional: 0.1%, 1%, Lutron, and Fifth Light DALI, LumaWatt Pro and WaveLinx connected lighting platforms available, Linear spread lens, soft focus lens, hex louver, and snoot option, Chicago plenum and emergency battery options

Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	6.76 W	CRI	80
Total flux	629 lm	LOR	100%
Luminous efficacy	93 lm/W	Total power	6.76 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.39 in Diameter: 2.00 in

Adjustability

Fixed

Electric

System power: 6.76 W

Protection

IP: 47