


Product data sheet

LED DOWNLIGHTS
V1-RF-90084-10D01-6503030 DL-01 11 W 30W 3000K DALI
VARTON




IP
65

IK
08

Classic dust-tight downlight. Paintable in any RAL color. Application: healthcare, offices, commercial spaces, hospitality (restaurants, hotels, coffee bars), retail spaces. Installation: recessed into plasterboard, stretch or suspended ceilings. Input voltage (AC, 50Hz): 198...264 AC frequency: 50 Flicker: 1 Climatic modification and category of placement: YXЛ4 Protection class: II Housing material: Aluminium Mounting method: Built-in Ingress protection (IP): IP65 Impact resistance: IK08 https://www.varton.ru/products/daunlayty/dl-01-rus/dl-01-rus-slim-200/svetodiodnyy-svetilnik-varton-dl-01-slim-200-mm-30-vt-3000-k-kruglyy-vstraivaemyy-221x40-mm-ip65-40-_8/

Light output 1



1 x LED			
Nominal lamp power	30 W	LOR	100%
Lamp flux	2880 lm	Total flux	2880 lm
Luminous efficacy	96 lm/W	Total power	30 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 1.57 in
Diameter: 8.70 in

Adjustability

Fixed

Electric

System power: 30 W

Protection

IP: 65
IK: 08