# Product data sheet

LED DOWNLIGHT SERIES DLE 18W 4000K DLE-18N

MPE








- Round shape Recessed mounted on ceiling or use additional SRDLE accessories for floating mounting Driver is integrated inside the light.
- Size: Ø216 x 55mm Cut out: Ø200mm Voltage: 100-240VAC Power: 18W Power Factor (PF): >0.5 Luminance: 1800 lm Color Temperature (CCT): 4000-4500K RA >80 High Color Rendering Index Beam angle: 110° Chip LED: SMD 2835 Life Time: 30,000 hours Instant Light: 0s European Standard CE RoHS

### Light output 1



1 x LED	
Nominal lamp power	
Lamp flux	18
Luminous efficacy	100
CCT	۷
CRI	

18 W	LOR	100%
1800 lm	Total flux	1800 lm
00 lm/W	Total power	18 W
4000 K		
88		

## Mounting mode

Ceiling recessed

#### Shape and measurements

Length: 46.26 in Width: 3.54 in Height: 3.66 in

## Adjustability

Fixed

#### Design

Material impression: Plastic

Designer: TREVOS

#### Glare protection

Glare protection: UGR < 19

#### Electric

System power: 18 W

Ballast: ECG

#### Protection

IP: 20

Designation labels: CE, ENEC

## Other operating numbers

Ambient temperature range: -13...122°F