Product data sheet

ACTOR G2 CEILING OP VIT DIM 400MA 4000K
7028516
HIDE-A-LITE

Actor G2 Ceiling is a surface-mounted ceiling luminaire. Its clean, edge-aligned design blends seamlessly into the ceiling for a discreet look—ideal for spaces where the light should be visible but not dominant. The built-in DIP switch allows you to adjust the colour temperature directly on site. No need to plan everything in advance; the light can be fine-tuned after installation. The modular construction means you only replace the necessary part. Actor G2 Ceiling is perfect for corridors, entrances, and for wall or picture lighting. It can be installed individually, linked into continuous light lines, or arranged in patterns that follow the room's shape. Each luminaire acts as both leader and follower. For suspended mounting, a separate suspension kit is available, providing downlight only. Choose from a range of glare shields to adapt the light to the setting: opal, microprismatic, double parabolic or asymmetric or highlighting walls and artwork.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	20 W	CRI	90
Total flux	2787 lm	LOR	100%
Luminous efficacy	139 lm/W	ULOR	8%
		Total power	20 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 44.53 in
Width: 2.05 in
Height: 3.07 in

Adjustability

Fixed

Design

Color of housing: White
Designer: Elektro Elco AB

Electric

System power: 20 W
Color adjustable
Appliance Class: I

Protection

IP: 20
Designation labels: CE