Product data sheet

NADJA I (WALL FITTING) 9.840.3046.05

LEIPZIGER LEUCHTEN




Recommended mounting height 4.00 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge Voltage: 230V

IP 55

50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp					
Nominal lamp power	50 W	LOR			
Lamp flux	2000 lm	Total flux			

Lamp flux	2000 lm	Total flux	1543 lm
Luminous efficacy	26 lm/W	Total power	59 W
CCT	3400 K		
CRI	54		

7-1-1-1	12AH
\mathcal{K}	$\mathbb{P} \setminus \mathbb{X}$
XX	
	H
\checkmark	-+
4	

1 x High pressure mercury vapour lamp						
Nominal lamp power	80 W	LOR	77%			
Lamp flux	4000 lm	Total flux	3087 lm			
Luminous efficacy	35 lm/W	Total power	89 W			
CCT	3400 K					
CRI	54					

Mounting mode Wall mounted Shape and measurements

Height: 20.08 in Diameter: 20.08 in

Electric

System power: 59-89 W

Protection

IP: 55

77%