

# Product data sheet

CLARICO DOWN HB-D 830 DALI CLO  
23818-529  
FAGERHULT



Installation Recessed mounting in ventilated or unventilated suspended ceilings. Two optional designs. VTB – for suspended ceilings with visible T-bars 25 mm. 300x300 also for fixed suspended ceilings. HB – for suspended ceiling with concealed T-bars. Supplement with fixing brackets for fixed suspended ceiling, see accessories. The luminaire must not be covered with insulation. For further details please refer to the assembly instructions on our website Connection Connection in ballast box. The ballast box can be detached and positioned next to the luminaire. Snap-in terminal block 3x1,5 mm<sup>2</sup> (5x1,5 mm<sup>2</sup> where dimming is required). Design Luminaire body in white enamelled sheet steel (RAL 9016). Louvre A combination of microprismatic and frosted opal surfaces in acrylic (PMMA) with a thin opal diffuser (PMMA) on the inside. Miscellaneous Enclosure class IP 44 under suspended ceilings and IP 20 above suspended ceilings.

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	34 W	CRI	80
Total flux	3875 lm	LOR	100%
Luminous efficacy	114 lm/W	Total power	34 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 23.58 in  
Width: 23.58 in  
Height: 2.37 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 34 W

## Protection

IP: 44