Product data sheet

LUCAS X (1-ARMED BEADED) 9.850.3066.16

LEIPZIGER LEUCHTEN









Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately inquire separately for pole to suit double-bracket luminaire Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp					
Nominal lamp power	125 W	LOR			
Lamp flux	6800 lm	ULOR			
Luminous efficacy	41 lm/W	Total flux			
CCT	3400 K	Total power			
CRI	54				



1 x High pressure mercury vapour lamp				
Nominal lamp power	80 W	LOR	83%	
Lamp flux	4000 lm	ULOR	2%	
Luminous efficacy	37 lm/W	Total flux	3316 lm	
CCT	3400 K	Total power	89 W	
CRI	54			

Mounting mode

Pole top mounted

Shape and measurements

Height: 19.69 in Diameter: 22.44 in Electric

System power: 89-137 W

Protection

IP: 55

83% 2% 5637 lm 137 W