# Product data sheet

LIGHTALK 7 WALL WASHER FLOODLIGHTS LA-30013-VN-40

LIGMAN









- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour RGBW 30,40,65 - Die-cast aluminium end-caps, extruded aluminium housing and aluminium front frame pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Integral control gear for LA-30001, LA-30002, LA-30013, LA-30014 - Remote driver is included for LA-30021, LA-30022

#### Light output 1 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	9.2 W	CRI	80
Total flux	676 lm	LOR	100%
Luminous efficacy	73 lm/W	ULOR	100%
		Total power	9.2 W

#### Light output 2 (integrated)




Lamp type	LED	CCT	0 K
Nominal lamp power	8.8 W	CRI	-50
Total flux	92 lm	LOR	100%
Luminous efficacy	10 lm/W	ULOR	100%
		Total power	8.8 W

#### Light output 3 (integrated)



Lamp type	LED	CCT	7247 K
Nominal lamp power	9.3 W	CRI	-18
Total flux	548 lm	LOR	100%
Luminous efficacy	59 lm/W	ULOR	100%
		Total power	9.3 W

## Light output 4 (integrated)



Lamp type	LED	CCT	0 K
Nominal lamp power	7 W	CRI	-29
Total flux	384 lm	LOR	100%
Luminous efficacy	55 lm/W	ULOR	100%
		Total power	7 W

## Mounting mode

Wall mounted, Floor mounted

## Shape and measurements

Length: 3.54 in Width: 23.86 in Height: 2.56 in Weight: 3.8 kg

## Adjustability

Free

## Design

Color of housing: Black, White, Silver gray

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 34.3 W Voltage: 230 V AC Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

## Protection

IP: 67 IK: 10

Surface temperature: 40°C