


Product data sheet

PENDANT LUMINAIRE MILANO SLIM ROUND CRI > 80 4000K 15W
2004.2491 - MILANO S PEN430-3100 LED2400-840 DID DALI
REGENT



Pendant luminaire Milano Slim round, with LED, standby power 0.5 W, colour rendering index CRI > 80, 4000 K, system power: 15 W, neutral white, luminous flux of luminaire 2400 lm, colour tolerances SDCM 3, lifetime LED L80 50'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, direct-indirect light emission (58%/42%), opal, 1 integral control gear, DALI, pendant suspension kit to be ordered separately, protection class I, ingress protection IP40, glow wire test 650 °C, impact strength: IK 04, this product contains a light source of energy efficiency class A and EPREL registration number: 1397127 Ø = 430 mm, H = 81 mm, p = 3100 mm

Light output 1



1 x LED			
Nominal lamp power	15 W	LOR	100%
Lamp flux	2400 lm	ULOR	42%
Luminous efficacy	160 lm/W	Total flux	2394 lm
CCT	4000 K	Total power	15 W
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 16.93 in

Width: 16.93 in

Height: 3.39 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 15 W

Appliance Class: I

Protection

IP: 40

IK: 04