

# Product data sheet

SPOT LIGHT IP65 1X 3W TRILED RGB - 30 DEG


L17318B

PROLED (MBN GMBH)




The PROLED SPOT LIGHT IP65 is suitable for emphasis lighting indoors as well as outdoors. Combined with a ground spike it is also perfect for plant and garden lighting. - dimmable, autom. colour change, controllable via DMX 512, DALI, KNX, 1-10V, CASAMBI, RF by MULTI power supplies or PRO CONTROLLER

## Light output 1 (integrated)




Lamp type	LED	CCT	0 K
Nominal lamp power	1.2 W	CRI	-29
Total flux	40 lm	LOR	100%
Luminous efficacy	33 lm/W	Total power	1.2 W

## Light output 2 (integrated)



Lamp type	LED	CCT	7247 K
Nominal lamp power	1.6 W	CRI	-18
Total flux	80 lm	LOR	100%
Luminous efficacy	50 lm/W	Total power	1.6 W

## Light output 3 (integrated)



Lamp type	LED	CCT	0 K
Nominal lamp power	1.5 W	CRI	-50
Total flux	30 lm	LOR	100%
Luminous efficacy	20 lm/W	Total power	1.5 W

**Mounting mode**

Standing / Bollard

**Shape and measurements**

Length: 3.43 in

Width: 2.60 in

Height: 3.19 in

Weight: 0.4 kg

**Adjustability**

Rotatable, Tilttable

**Electric**

System power: 4.3 W

Appliance Class: III

**Protection**

IP: 65

IK: 02

**Other operating numbers**

Ambient temperature range: 14...113°F