
Product data sheet


HALO CENTRALIZED SUSPENSION BLACK 1220MM
R48Z122-9005C1830H3S
PLANLICHT



IP 20 CE


LED HO 3000K 67W 4637lm DALI https://katalog.planlicht.com/en-us/fam-halo/

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	8.38 W	CRI	80
Total flux	580 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	8.38 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	8.38 W	CRI	80
Total flux	580 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	8.38 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	8.38 W	CRI	80
Total flux	580 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	8.38 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	8.38 W	CRI	80
Total flux	580 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	8.38 W

Light output 5 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	8.38 W	CRI	80
Total flux	580 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	8.38 W

Light output 6 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	8.38 W	CRI	80
Total flux	580 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	8.38 W

Light output 7 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	8.38 W	CRI	80
Total flux	580 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	8.38 W

Light output 8 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	8.38 W	CRI	80
Total flux	580 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	8.38 W

Mounting mode

Pendant

Shape and measurements

Length: 48.03 in
Width: 48.03 in
Height: 2.17 in

Adjustability

Fixed

Electric

System power: 67 W

Protection

IP: 20
Designation labels: CE