


Product data sheet

FUTURA 2.5FT ABS AL 8000/840 DALI
77083
TREVOS



unique design, resistant against humidity and dust, with IP66 enclosure rating and built-in aluminium heat sinks; optimal mounting height: 3.5 to 10 m; digitally dimmable DALI driver (AC/DC); Body: dark grey ABS (high chemical resistance, UV stability, RAL 7001); Diffuser: translucent acrylic (AC), UV stable, chemically resistant; Reflector: steel sheet, white (RAL 9003); Clips: polyamide + 15 % fibreglass; Sealing: polyurethane (PUR), foam-filled base groove; Connection: screwless five-pole terminal block; Power: 48,3 W; Luminaire flux: 7330 lm; Lifetime: L90/B10; 50000 hours; Impact strength: IK06; Ambient temperature: -25|50 °C; Weight: 3,05 kg;

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	48.3 W	CRI	80
Total flux	8330 lm	LOR	100%
Luminous efficacy	172 lm/W	ULOR	4%
		Total power	48.3 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 57.17 in

Width: 5.71 in

Height: 4.41 in

Adjustability

Fixed

Design

Material impression: Plastic

Color of housing: Silver gray, White

Designer: TREVOS

Electric

System power: 48.3 W

Ballast: ECG

Controller: DALI

Appliance Class: I

Protection

IP: 66

IK: 06

Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -13...122°F