Product data sheet


SAFESITE LED AREA LIGHT 6800 LUMENS, WIDE DISTRIBUTION, TEMPERED GLASS LENS
ALC7WN27-XXXXX-N
DIALIGHT



IP 66 IK 07

SafeSite LED Area Light 6,800 Lumens 64 Watts 100-277V AC, 120-250V DC Neutral White, 80CRI Tempered Glass Lens Class I Div 1 Groups B,C,D Class II Div 1 Groups E,F,G Class III Div 1&2 UL 844 UL 1598/A CSA C22.2 No. 137-M81 NEMA 4X Factory Sealed IK07 Wide Distribution IP66/67/69 Scaled IES File

Light output 1 (integrated)



Lamp type	LED	CCT	3783 K
Nominal lamp power	63.7 W	CRI	80
Total flux	6800 lm	LOR	100%
Luminous efficacy	107 lm/W	Total power	63.7 W

Mounting mode

Pendant

Shape and measurements

Length: 10.71 in
Width: 9.69 in
Height: 5.71 in

Adjustability

Rotatable, Tiltable

Electric

System power: 63.7 W
Voltage: 100 V AC, 277 V AC, 120 V DC, 250 V DC
Appliance Class: I

Protection

IP: 66
IK: 07