# Product data sheet

LDRT6B/LDRT67B LED 6" ROUND RETROFIT DOWNLIGHT LD6B10D010 EU6B10209024 6LBSW1LI


COOPER LIGHTING





Retrofit, remodel; International installation; Install from below, Excellent light control and low aperture brightness, Available for shallow or standard plenums; ENERGY STAR® qualified, Round die-cast or spun aluminum reflectors, 6 color temperatures: 2400K, 2700K, 3000K, 3500K, 4000K and 5000K CCT, CRI: 80, 90 or 97; D2W<sup>™</sup> option from 3000K to 1850K, W2N Tunable White 2700K-6500K or 2000K-5000K, Lumens: 1,000-7,000; 0-10V dimming down to 1%, WaveLinx and DLVP connected lighting systems compatibility, 5-year warranty

#### Light output 1 (integrated)



Lamp type	LED	CCT	2400 K
Nominal lamp power	10.05 W	CRI	90
Total flux	977 lm	LOR	100%
Luminous efficacy	97 lm/W	Total power	10.05 W

## Mounting mode

Ceiling recessed

### Shape and measurements

Height: 0.39 in Diameter: 5.50 in

## Adjustability

Fixed

## Electric

System power: 10.05 W

## Protection

IP: 47