Product data sheet


LUPALO SCANDIA
612264.0031.1.76
RZB



IP 66 IK 06

Series: LUPALO SCANDIA Pole-top luminaire with classic design and modern LED technology. Housing made of corrosion-resistant die-cast aluminium, seawater-resistant powder-coated (C4, in accordance with ISO 12944-6). C5 coating available on request. Stainless steel screws. Membrane valve to prevent condensation. Non-yellowing clear glass cylinder. LED module with optimised optic lenses for sophisticated lighting solutions. Asymmetrical linear light distribution for wide streets and paths according to EN 13201. Pole attachment for 76 mm spigot. Control gear with integrated surge protection. 4 x 1.0 mm² connecting cable included, length 8 m. Please order reducer adapter for pole clamp D 60 mm separately. Order the top roof separately as an accessory for the classic lantern shape. Colour: anthracite metallic (DB703) Diameter: 187 mm Height: 572 mm Lamp: LED System power: 35 W Rated luminous flux: 3850 lm Luminous efficiency: 110 lm/W Control gear: Converter, dimmable, DALI Protection class: II Type of protection: IP 66

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	35 W	CRI	70
Total flux	3850 lm	LOR	28%
Luminous efficacy	110 lm/W	ULOR	8%
		Total power	35 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 22.52 in
Diameter: 7.36 in

Adjustability

Fixed

Electric

System power: 35 W

Protection

IP: 66
IK: 06