
Product data sheet


LED DOWNLIGHTS
V1-R0-70254-20L36-2001440 DL-BOX REFLECT MULTI 2X2 MEDIUM 14W 4000K
VARTON



IP 20 IK 01

Input voltage (AC, 50Hz), V: 198...264 AC frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: УХЛ4 Protection class: II Housing material: Aluminium Mounting method: Surface mounting Ingress protection (IP): IP20 Impact resistance: IK01 Power factor: 0,95 https://www.varton.ru/products/daunlayty/dl-box-reflect/dl-box-reflect-multi-2x2-medium/svetodiodnyy-svetilnik-varton-dl-box-reflect-multi-14-vt-2x2-nakladnoy-4000-k-80kh80kh150-mm-ral7045_8/

Light output 1



1 x LED

Nominal lamp power	14 W	LOR	100%
Lamp flux	1350 lm	Total flux	1350 lm
Luminous efficacy	96 lm/W	Total power	14 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 3.15 in
Width: 3.15 in
Height: 5.91 in

Adjustability

Fixed

Electric

System power: 14 W

Protection

IP: 20
IK: 01