
Product data sheet


PURE3.QUIET SUSP. ANTHR./SILVER L DI/ID HE PRISM
P33H34R-QASIC2940L1T OHNE FOLIE/WITHOUT FOIL
PLANLICHT



IP 20


LED LO 4000K 152,6W 24341lm CRI90 ¹Values without foil [Luminaire is delivered with optional satined-foil for increased homogenity. The light distribution is thus influenced and the luminous flux is reduced by 7,3% https://katalog.planlicht.com/en-gb/search?q=pure%203

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	38.15 W	CRI	90
Total flux	6085 lm	LOR	100%
Luminous efficacy	160 lm/W	ULOR	34%
		Total power	38.15 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	38.15 W	CRI	90
Total flux	6085 lm	LOR	100%
Luminous efficacy	160 lm/W	ULOR	34%
		Total power	38.15 W

Light output 3 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	38.15 W	CRI	90
Total flux	6085 lm	LOR	100%
Luminous efficacy	160 lm/W	ULOR	34%
		Total power	38.15 W

Light output 4 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	38.15 W	CRI	90
Total flux	6085 lm	LOR	100%
Luminous efficacy	160 lm/W	ULOR	34%
		Total power	38.15 W

Mounting mode

Pendant

Shape and measurements

Length: 27.95 in
Width: 137.80 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 152.6 W

Protection

IP: 20