Product data sheet

CUBIC AMBIENT SUSPENDED - P7
CP7FEE-830M-Q400-K
LIGHTNET



LED pendant luminaire. Omnidirectional light distribution. Luminaire body made of aluminium. Surface natural anodised or white, graphite, black or champagne coated. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Ambient diffuser made of frosted acrylic glass for general lighting. Driver integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperature 2700K, 3000K, 3500K or 4000K. Binning initial ≤ MacAdam 3. Colour rendering CRI>80 or CRI>90. Height-adjustable parallel-cord suspension with transparent power supply cable. On request: Integration of emergency lighting components, sensor technology, soft-touch black or red sheathed power supply cable.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	19 W	CRI	82
Total flux	3142 lm	LOR	100%
Luminous efficacy	165 lm/W	ULOR	25%
		Total power	19 W

Mounting mode

Pendant

Shape and measurements

Length: 15.75 in
Width: 15.75 in
Height: 2.36 in

Adjustability

Height adjustable

Electric

System power: 19 W

Protection