


Product data sheet

SLOIN A SL LED2000-830 L1524 PCO
42184236
ZUMTOBEL



LED light line with DALI-controllable LED converter; LED service life lasts 50000 h before luminous flux is reduced to 90% of the initial value. Chromaticity tolerance (initial MacAdam): 3. Luminaire luminous flux: 2030 lm, Luminaire efficacy: 82 lm/W. Colour rendering Ra > 80, colour temperature 3000 K. PC cover with anti-glare film for standard-compliant workstation illumination with UGR<19 and L65<3000 cd/m² (EN: 12464:2011). Luminaire of aluminium, silver powder coated. Luminaire with completely uniform appearance due to polycarbonate cover. Luminaire consists of housing and continuous optic of polycarbonate. Includes gear tray, wiring, and end-cap set. Luminaire wired with halogen-free leads and covers are due to norm classified as TP(a). Degree of protection: IP40 below (IP20 above). Dimensions: 1524 x 76 x 98 mm weight: 6.5 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	24.8 W	CRI	80
Total flux	2030 lm	LOR	100%
Luminous efficacy	82 lm/W	Total power	24.8 W

Mounting mode

Pendant

Shape and measurements

Length: 60.00 in
Width: 2.99 in
Height: 3.86 in
Weight: 6.5 kg

Design

Material impression: Aluminum
Color of housing: Silver gray

Electric

System power: 24.8 W
Voltage: 220-240 V AC
Controller: DALI
Appliance Class: I

Protection

IP: 40
IK: 07
Designation labels: CE, ENEC