


Product data sheet

NEOS
2356-K-4-667-XX
UNILAMP



NEOS NEOS is a small sized high performing area light. Outstanding optical efficacy, high ambient temperature rating and a wide range of mounting accessory makes NEOS a highly competitive product. The smooth curved design eliminates accumulation of water and dust. The unobtrusive slim design is a great match for commercial and residential lighting tasks. The area light can be either equipped with a photocell, DALI-2 control or basic on-off control gear. NEOS can be equipped with mounting accessories for pole integrated mounting, pole bracket, wall and wall corner. The pole bracket is suitable for Pole diameters up to 105mm. Features: • Photocell for simple and cost effective light management • Easy spec: one luminaire part code multiple mounting options • Supreme surge protection: mains and dimming line 10kV protected • Prewired cable 2000mm

Light output 1



1 x LED			
Nominal lamp power	32 W	LOR	9%
Lamp flux	6080 lm	Total flux	525 lm
Luminous efficacy	190 lm/W	Total power	32 W
CCT	4000 K		
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Length: 2.76 in
Width: 1.89 in
Height: 4.01 in

Adjustability

Tiltable

Electric

System power: 32 W
Controller: Dimmable 1..10V
Appliance Class: I

Protection

IP: 66
IK: 08