



Product data sheet

GUIDELED SL 13031 CG-S
40071353481
EATON EMERGENCY LIGHTING



• Safety luminaire in LED technology for recessed mounting • Low installation depth of only 38 mm • Almost flush appearance on the ceiling ensured by optics integrated in the luminaire • Suitable for mounting heights up to 28 m by narrow beam optics and exceptionally efficient HighPower LEDs • Spacing up to 24 m from luminaire to luminaire with optics for escape route illumination • Up to 15 m from luminaire to luminaire with optics for open area illumination • Minimum service requirement due to high service life of the LEDs (50 000 hours)

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	6500 K
Nominal lamp power	5 W	CRI	70
Total flux	168 lm	LOR	100%
Luminous efficacy	34 lm/W	Total power	5 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.94 in
Width: 3.94 in
Height: 1.50 in
Weight: 4.3 kg

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 5 W
Appliance Class: II

Information regarding emergency functions

Emergency lighting only
Emergency power supply: Central battery feed-in
Emergency sign: N/A

Protection

IP: 41
IK: 03
Designation labels: CE