
Product data sheet


X-LINE SLIGHT LOW UGR L-DOWN LED 3000 LOUVER EDD 21 830 / L-2000MM S-1,5M
19.4084.4413.21
LUXIONA



IP 40 IK 04

Indoor luminaire. Assembly: surface mounted on slings. The body material is aluminum. Colour - RAL 9006 (grey). Dimensions: 2000 x 34 x 68 mm. Diffuser: LOUVER (anti-glare louver). The efficiency of the optical system is 71,66%. Beam angle: (C0-C180) / (C90-C270) - 46° / 44,6°. Light source type: LED. Colour of the light 3000 K. SDCM=3. CRI>80. Lifetime of LED sources: 145000 h L90/B10. Luminaire luminous flux: 2116,9 lm. Power of luminaire: 18,2 W. Luminaire's light efficiency: 116,3 lm/W. Driver: DIM DALI (EDD). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 17 (B10), 28 (B16), 26 (C10), 41 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



1 x LED

Nominal lamp power	18.2 W	LOR	52%
Lamp flux	2952 lm	Total flux	1548 lm
Luminous efficacy	162 lm/W	Total power	18.2 W
CCT	3000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 78.74 in
Width: 1.34 in
Height: 2.68 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 18.2 W
Controller: DALI
Appliance Class: I

Protection

IP: 40
IK: 04

Other operating numbers

Ambient temperature range: 41...95°F