Product data sheet

STARBEAM - AREA STANDARD DISTRIBUTION - 85W - 4000K - SMARTSCAN EMERGENCY
WSB085A40
THORLUX LIGHTING



IP 66

LED area floodlights and streetlights Supremely efficient and optically versatile, IP66 pole-top and wall-mounted LED luminaires comprised of marine-grade LM6 aluminium alloy body and high transmission toughened glass cover for maximised LED efficiency and optical distribution. The patented MountSet fixing method enables Starbeam to be mounted onto a wide array of column and bracket sizes without the need for additional reducers or inserts, and easily installed with tool-free access. Starbeam is available in a varied selection of light distributions suitable for both open areas and roadway applications, allowing it to be implemented into designs seamlessly. Applications: car parks, amenity areas, walkways, general roadways, access roads, loading areas/yards

Light output 1 (emergency)



1 x LED

Nominal lamp power	85 W	LOR	100%
Lamp flux	14105 lm	ULOR	11%
Luminous efficacy	160 lm/W	Total flux	14105 lm
CCT	4000 K	Total power	88 W
CRI	70		

Mounting mode

Pole top mounted

Shape and measurements

Length: 10.71 in
Width: 26.02 in
Height: 6.14 in

Adjustability

Tiltable

Electric

System power: 88 W

Information regarding emergency functions

Emergency lighting only
Emergency sign: N/A

Protection

IP: 66