
Product data sheet

FEMTOLINE W DOWN-UP 1200 930 270 63 12 93


DELTA LIGHT





Luminaire, wall surface mounted (indoor use) from Deltalight, named FEMTOLINE W DOWN-UP 1200 930, available in the colour(s): black, white. This luminaire is equipped with 2 x (LED FLEX IN MP 12W / CRI>90 / 3000K / 1248lm) with build-in driver to operate on a voltage of 220-240V / 50-60Hz. Not dimmable Light distributor: opal diffuser.

Light output 1



1 v I FD

I X LED			
Nominal lamp power	42 W	LOR	73%
Lamp flux	3360 lm	Total flux	2444 lm
Luminous efficacy	80 lm/W	Total power	42 W
CCT	3000 K		
CRI	90		
1 x LED			
Nominal lamp power	42 W	LOR	73%
Lamp flux	3360 lm	Total flux	2444 lm
Luminous efficacy	80 lm/W	Total power	42 W
CCT	3000 K		
CRI	90		

XXF	FXX
HTT	PKTH
XXF	FXX

Mounting mode Wall mounted

Length: 47.24 in Width: 1.10 in

Height: 3.07 in

Weight: 1.6 kg

Shape and measurements

T	Luminous efficacy	80 lm/W	Total power	
	CCT	3000 K		
	CRI	90		
Electric				

System power: 42 W Appliance Class: 0

Protection

IP: 20 Designation labels: CE