


Product data sheet

UNO 1100 GRAPHITE 420LM 3000K RA>80 TRAILING EDGE DIMMING
7021986436402
SG ARMATUREN



Attractive, round wall luminaire with half-diffuser and slit that can be installed both indoors and outdoors. Made of die-cast powder-coated aluminium. Diffuser made of UV-stabilised opal polycarbonate. Two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. Variants with integrated Twilight relay. Corrosion-proof with 10-year warranty, IP65 and vandalresistant rating IK10. Light distribution Direct Light technic LED 10W 3000K Ra>80 SDCM 3 L70/B50 >50,000 hrs Control/Dimming Trailing edge dimming Protection Class II IP65 IK10 Fire protection class: 850°C - 30s Materials and finish Housing: Aluminium Colour: Graphite Optics: UV-stabilized polycarbonate Mounting/Connection Surface, Indoor / Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 33, B16: 52, C10: 40, C16: 64

Light output 1



1 x LED			
Nominal lamp power	10 W	LOR	100%
Lamp flux	420 lm	ULOR	7%
Luminous efficacy	42 lm/W	Total flux	420 lm
CCT	3000 K	Total power	10 W
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Length: 10.63 in
Width: 4.84 in
Height: 10.63 in

Adjustability

Fixed

Electric

System power: 10 W
Appliance Class: II

Protection

IP: 65
IK: 10