

# Product data sheet

LINA\_LED\_2X15W\_NEUTRAL\_L660MM


511873

PETRIDIS



Technical Features - Luminaires for Led lamp or Led modules version. - Ecologic anti-aging injected sealing gasket. - Gear-tray reflector unit in hot-galvanized steel, painted in white polyester, fixed to the housing by means of steel rapid devices, hinged opening. - Snug fit snap-lock clips in polycarbonate for diffuser mounting. - Stainless steel fixing brackets. - Connection for operation on 230V-50Hz. - Ra≥80, 3000K, 4000K. - Led life time 50000h (L80B10). - Driver life time 100000h. - Colour tolerance: 3 MacAdam steps. Upon request - Connection for operation on 230V-50/60Hz with dimmer dali or 1-10VDC ballast. - Connection for emergency lighting system, for one or three hours.

## Light output 1



1 x LED

Nominal lamp power	30 W	LOR	88%
Lamp flux	5044 lm	Total flux	4441 lm
Luminous efficacy	168 lm/W	Total power	30 W
CCT	4000 K		
CRI	80		

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 25.98 in

Width: 6.30 in

Height: 4.33 in

## Adjustability

Fixed

## Design

Material impression: Plastic

## Electric

System power: 30 W

Appliance Class: I

## Protection

IP: 66

IK: 10

Resistant to impact of balls

Designation labels: CE, ENEC