
# Product data sheet


LINEDO_2,3M_AD_1111
9523AD.852.400.002
RZB



IP 54 IK 03


LINEDO, 84 W, 12600 lm, 850, white, on/off Continuous line luminaire, L 2291 B 58 H 76

## Light output 1 (integrated)




| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 5000 K |
| Nominal lamp power | 21 W | CRI | 80 |
| Total flux | 3150 lm | LOR | 100% |
| Luminous efficacy | 150 lm/W | Total power | 21 W |

## Light output 2 (integrated)




| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 5000 K |
| Nominal lamp power | 21 W | CRI | 80 |
| Total flux | 3150 lm | LOR | 100% |
| Luminous efficacy | 150 lm/W | Total power | 21 W |

## Light output 3 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 5000 K |
| Nominal lamp power | 21 W | CRI | 80 |
| Total flux | 3150 lm | LOR | 100% |
| Luminous efficacy | 150 lm/W | Total power | 21 W |

Light output 4 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 5000 K |
| Nominal lamp power | 21 W | CRI | 80 |
| Total flux | 3150 lm | LOR | 100% |
| Luminous efficacy | 150 lm/W | Total power | 21 W |

### Mounting mode

Ceiling mounted

### Shape and measurements

Length: 2.28 in
Width: 90.20 in
Height: 2.99 in

### Adjustability

Fixed

### Electric

System power: 84 W

### Protection

IP: 54
IK: 03