



Product data sheet

3461 DENIA PRO 2 - LM - L-H<LT/>1 4000K CRI 70 75W CLD GREY9007
340026-0054-0200-LM
DISANO



Housing: in die-cast aluminium and designed with a very small surface exposed to wind. Cooling fins integrated in the cover. Attachment: in die-cast aluminium with clamps for fastening the fixture at different angles. Diffuser: extra-clear, tempered glass, 4 mm thick, resistant to thermal shock and impact (UNI-EN 12150-1:2001). Coating: pre-treatment of metal surface, polyester powder coating to ensure resistance to corrosion and salt spray fogs, UV stabilised. Heat Sink: integrated Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Laboratory tests: compliant with third-party certified vibration tests pursuant to ANSI C136.31: Street Lighting - Luminaire Vibration. Test level: 3.0G Level 2 for bridge/overpass applications.

Light output 1



1 x LED			
Nominal lamp power	75 W	LOR	100%
Lamp flux	12296 lm	Total flux	12296 lm
Luminous efficacy	164 lm/W	Total power	75 W
CCT	4000 K		
CRI	70		

Mounting mode

Pole top mounted

Shape and measurements

Length: 21.85 in

Width: 10.28 in

Height: 3.58 in

Adjustability

Fixed

Electric

System power: 75 W

Appliance Class: II

Protection

IP: 66

IK: 09

Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -22...104°F