

# Product data sheet

MINI ARGOS 1 - WALL DOWNLIGHT  
5401-0-3-422-XX  
UNILAMP




Robust and rectangular in appearance offer multi directions of light. ARGOS can illuminate both top and bottom at the same time or single vertical direction of either top or bottom. This is a wall light with simple geometric shape, which suitable for facade application thereof. ARGOS via precise manufactured achieve reliable IP65. LED is by way of Citizen and OSRAM with brilliant color rendering. As a result improves lumen efficiency output while maintaining conservation of energy economically. SPEC • Designed, Manufactured and Tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium housing. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Safety glass cover. • Post-cured silicone gasket. • High quality LED module and driver. • Optical glass lens. • GFR PA6.6 terminal block. • Weather proof grommet. • Installation work has to be carried on according to the enclosed product manual.

## Light output 1



### 1 x Compact fluorescent lamp

Nominal lamp power	13 W	Socket	G24D-1
Lamp flux	900 lm	LOR	18%
Luminous efficacy	69 lm/W	Total flux	159 lm
CCT	4000 K	Total power	16 W
CRI	85		



### 1 x Compact fluorescent lamp

Nominal lamp power	13 W	Socket	G24D-1
Lamp flux	900 lm	LOR	18%
Luminous efficacy	69 lm/W	Total flux	159 lm
CCT	3000 K	Total power	16 W
CRI	85		

## Mounting mode

Wall mounted

## Shape and measurements

Length: 8.86 in

Width: 4.19 in

Height: 3.54 in

## Adjustability

Fixed

## Electric

System power: 16 W

Appliance Class: I

## Protection

IP: 65

IK: 07