


Product data sheet

LUGTRACK 2 LED 3000 6000LM 3000K OPAL PLEXIGLASS (PLX) WHITE
080101.5L14.21
LUG



Modern LED luminaire for quick assembly, construction of the luminaire enables quick, easy and tool-less connection into long lighting systems (available in 1,5m and 3m-long dimension) by the usage of mounting elements. Mounting: suspended, on wire suspension (on request) Body: coated steel sheet Power: 220-240V 50/60Hz Lifetime (L80B10): 50 000 h Operating temperature range: 0°C ... +45°C Available on request: DALI, LED emergency module Additional information: Mounting bracket 150110.00654 - purchase only for installation of luminaire according to mounting instruction in variant B. The possibility of using one or more power supplies in the luminaire. Other remarks: through wiring 5x2,5mm (as a standard), connector (1 pcs.) with option of hook installation Warranty: 5 years Application: supermarkets, warehouses, production halls, logistics centers

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	52 W	CRI	80
Total flux	3000 lm	LOR	100%
Luminous efficacy	58 lm/W	Total power	52 W

Mounting mode

Pendant

Shape and measurements

Length: 118.11 in
Width: 5.08 in
Height: 2.24 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 52 W
Appliance Class: I

Protection

IP: 20
IK: 05