



Product data sheet

LADOR CLUSTER COLUMN PROJECTORS
LD-20003-N-W40-A52121
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Life time L90B10 Ta 25° 135,000 - Life time L80B10 Ta 50° 310,000 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Thermal heat dissipation body - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear - Maximum wind load resistance is 140 km/h - Surge protection 10 kV

Light output 1 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	38.9 W	CRI	80
Total flux	2696 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	38.9 W

Light output 2 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	38.9 W	CRI	80
Total flux	2696 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	38.9 W

Light output 3 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	38.9 W	CRI	80
Total flux	2696 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	38.9 W

Light output 4 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	38.9 W	CRI	80
Total flux	2696 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	38.9 W

Mounting mode

Standing / Bollard, Pole integrated

Shape and measurements

Length: 5.71 in
Width: 7.68 in
Height: 314.96 in
Weight: 39.4 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 155.6 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 66
IK: 08
Surface temperature: 40°C