


Product data sheet

JUPITER PRO 2200 GRAPHITE 40° 2200LM 4000K RA>90
940441
SG ARMATUREN



Pro LED downlight for indoor or outdoor mounting. Powerful lumen output via the powerful recessed LED chip. Driver surface-mounted with quick junction box with quick clips for additional looping. Made of die-cast powder-coated aluminium, glass diffuser. Light distribution Direct - Beam angle 40° Light technic LED (not exchangeable) 22W 4000K Ra>90 SDCM 2 L90/B10 >50,000 hrs at Ta=25°C Control/Dimming Trailing edge dimming Protection Class II SELV IP65 Energy and approvals A+ CE Materials and finish Housing: Aluminium Colour: Graphite Optics: Glass Mounting/Connection Recessed, Indoor / Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 35, B16: 57, C10: 58, C16: 95

Light output 1



1 x LED			
Nominal lamp power	22 W	LOR	100%
Lamp flux	2200 lm	Total flux	2200 lm
Luminous efficacy	100 lm/W	Total power	22 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 4.49 in
Width: 4.49 in
Height: 4.17 in

Adjustability

Fixed

Electric

System power: 22 W
Appliance Class: II

Protection

IP: 65