Product data sheet

LGS01051002LINGQINGIIDAN-5W-MW-24°-4000
140058023
OPPLE



Housing:Die casting aluminum,white; Reflector:polycarbonate with vacuum plating; Mounting ring:Die casting aluminum,white; Mounting location: Ceiling; 0°-30°vertical tilting angle adjustability; Power:5W; Lamp(s):LED 840; Colour temperature:4000K; Colour rendering:RA82; Total luminous flux of luminaire:375lm; Glare control:UGR<13; Service life:30,000h at 70% luminous flux; Degree of protection:IP20; Class of protection II; Mains voltage:220V/50Hz; Two fixing clips provided for tool-free installation in ceilings of thickness 1-25 mm; Dimensions:115×115×90mm; Ceiling cutouts:(95-100)×(95-100)mm;

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	5 W	CRI	80
Total flux	375 lm	LOR	100%
Luminous efficacy	75 lm/W	Total power	5 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 4.53 in
Width: 4.53 in
Height: 3.54 in

Adjustability

Free

Electric

System power: 5 W
Appliance Class: II

Protection

IP: 20
Designation labels: CCC