



Product data sheet

SURFACE BULKHEAD 250 SENSOR 10W/4000K BK IP65
4058075374980
LEDVANCE



Robust wall and ceiling luminaire with IP65 protection and high-frequency sensor. Product features: High frequency sensor for daylight and motion detection. UV-stabilized polycarbonate (PC) housing, PC-diffuser. Impact resistance: IK10. Push wire terminal for tool-free connection. Through-wiring possible. Type of protection: IP65. Luminous flux: up to 800 lm. High luminous efficacy: up to 80 lm/W. Lifetime (L70/B50): up to 50,000 h (at 25 °C). Ambient temperature in operation: -20...+40 °C. Product benefits: Multiple adjustments of sensor range, daylight detection and hold time. Suitable for use in dusty and damp locations thanks to high IP rating. Suitable for use in public areas thanks to high IK rating. Separate covers available for an aesthetic and functional product design. 5 years guarantee. Energy savings of up to 50 % (compared to luminaires that use fluorescent lamps). Areas of application: Direct replacement for luminaires with compact fluorescent lamps. Corridors, stairways, entrance areas. Passages, underpasses. Public areas. Equipment / Accessories: Additional cover rings in different designs available. Mounting screws and dowels included.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	926 W	CRI	80
Total flux	800 lm	LOR	100%
Luminous efficacy	1 lm/W	ULOR	3%
		Total power	926 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 11.22 in
Width: 10.24 in
Height: 2.76 in
Weight: 570 kg

Adjustability

Fixed

Design

Material impression: Plastic
Color of housing: Black

Electric

System power: 926 W
Appliance Class: II

Protection

IP: 65
IK: 10
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...104°F