


Product data sheet

INDUSTRIAL LIGHTING
V1-I0-70632-04L02-6510050 OLYMP 2.0 GL 100 W 100W 5000K 30°
VARTON



Medium-power Industrial luminaire with wide range of wattage and optics. Housing: heatsink made of extruded aluminum, assembly and mounting elements made of steel. Secondary optics - PMMA/PC. Tempered glass. Installation: Surface-mounted using an adjustable bracket. Angle of rotation: 0° to 180°, step of 7,5°. The luminaire has a wire for connecting to the mains. Wire length 0.3 meters. Application: Outdoor areas. Industrial facilities. Warehouses and fire hazardous zones classified as P-IIa according to Electrical Installations Regulations. Power factor: 0,95 Input voltage (AC, 50Hz), V: 100...305 AC frequency, Hz: 50 Input voltage (DC), V: 130...300 Flicker, %: 5 Climatic modification and category of placement: YXЛ1 Protection class: I Ingress protection (IP): IP65 Impact resistance: IK08
<https://www.varton.ru/products/promyshlennoe-osveshchenie/olymp-gl-2-0/olymp-gl-2-0-100-vt/svetodiodnyy-svetilnik-varton-promyshlenny-olymp-gl-2-0-100-vt-5000-k-klass-zashchity-ip65-ugol-30-/>

Light output 1



1 x LED			
Nominal lamp power	100 W	LOR	100%
Lamp flux	14500 lm	Total flux	14489 lm
Luminous efficacy	145 lm/W	Total power	100 W
CCT	5000 K		
CRI	70		

Mounting mode

Ceiling mounted

Electric

System power: 100 W

Shape and measurements

Length: 14.17 in
Width: 7.20 in
Height: 6.69 in

Protection

IP: 65
IK: 08

Adjustability

Fixed