

Product data sheet


LED DOWNLIGHT DLB 5W 3000K
DLB-5V
MPE



IP
20

- Round shape - Recessed - mounted on ceiling - The lamp is cast aluminum monolithic, powder coated for fast heat dissipation - Detachable driver for easy connection - Lamp with silver rim - Size: Ø110 x 35 mm - Cut out: Ø74mm - Voltage: 100-240VAC - Power: 5W - Power Factor (PF): >0.5 - Luminance: 550 lm - Color Temperature (CCT): 2800-3200K - RA >80 High Color Rendering Index - Beam angle: 110° - Chip LED: SMD 2835 - Life Time: 30,000 hours - Instant Light: 0s - European Standard CE – RoHS

Light output 1



| | | | |
|--------------------|----------|-------------|--------|
| 1 x LED | | | |
| Nominal lamp power | 5 W | LOR | 100% |
| Lamp flux | 550 lm | Total flux | 550 lm |
| Luminous efficacy | 106 lm/W | Total power | 5.18 W |
| CCT | 3000 K | | |
| CRI | 82 | | |

Mounting mode

Ceiling recessed

Shape and measurements

Length: 4.33 in
Width: 4.69 in
Height: 1.38 in

Adjustability

Fixed

Electric

System power: 5.18 W

Protection

IP: 20