


Product data sheet

PARSA-PSO/1200 LED - DIFFUSOR OPAL | OPAL DIFFUSER
4500 840 IP65 DALI2 HG (56612026610)
REGIOLUX



Luminaire with a higher protection rating; Housing made of glass-fibre reinforced polyester, with PUR foam age-resistant sealing in the surrounding edge, stainless steel diffuser clips, gear tray made of sheet steel painted white. Silicone-free seal and housing with increased chemical resistance. Housing colour light grey; Light distribution direct distribution by means of Opal diffuser of acrylic glass, deep-drawn acrylic glass diffuser with an opal smooth surface. The light source and driver are removable in accordance with the EU 2019/2020 ecodesign requirements and can be replaced in the factory. Integrated driver. Electrical connection via 5-pole connection terminal with plug-in contacts.. Swivel mounting bracket SBB to be ordered separately. Dimensions (LxWxH): 1300mm x 105mm x 117mm Cable entry KE (X/Y): 650mm/0mm Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 4000K Colour tolerance: 3SDCM Photobiological safety (Luminaire): RG0 LED service life: 50000h L80/B10 (Tq 25°C) Nominal luminous flux: 4611lm Luminaire luminous efficiency: 149lm/W Controller: Electronic driver DALI2 (1 pcs.) System output: 31W Energy efficiency class/light source: C Mains voltage: 230V Mains frequency: 50Hz Impact resistance (IK rating): IK03 (0°C), IK04 (25°C) Ambient temperatur: ta 0°C to 25°C Special properties: Ready for IoT UGR lat./long.: 24.5 / 21.8 Certification mark: IP65, Protection class I, F, D, HACCP DIN10500/Food/IFS/BRC, Indoor, CE Warranty period: 5 years Regiolux GmbH Type: parsa-PSO/1200 LED 4500 840 DALI2 hg Article number: 56612026610 Product deep link: <https://www.regiolux.de/en/article/56612026610> General warranty conditions: www.regiolux.de/en/Service/Warranty

Light output 1 (integrated)



Lamp type		CCT	4000 K
Nominal lamp power	31 W	CRI	80
Total flux	4611 lm	LOR	100%
Luminous efficacy	149 lm/W	Total power	31 W

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 51.18 in
Width: 4.13 in
Height: 4.61 in

Design

Color of housing: Anthracite / graphite

Electric

System power: 31 W
Appliance Class: 0

Protection

IP: 65
IK: 04
Designation labels: CE