


# Product data sheet

R40

40425.002.1

RZB



IP  
40

IK  
02

Series: R40 Type of Protection: IP 40 Protection Class: I Voltage: - 250 / 0 - 60 Hz Base and end caps: plastic. Cover: crystal glass, hand-blown. With socket and surface switch. Available Colours: white Type of Installation: Wall (surface) Dimensions: L 355, B 55, H 80 Lamp: 2 x E14 max. 40 W Socket 1: E14 Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Beam Angle: 180°/111° Unified Glare Ratio: 23,4 EEC: A+ - E

## Light output 1



### 2 x Compact fluorescent lamp

|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 8 W     | Socket      | E27    |
| Lamp flux          | 400 lm  | LOR         | 81%    |
| Luminous efficacy  | 41 lm/W | ULOR        | 20%    |
| CCT                | 2700 K  | Total flux  | 651 lm |
| CRI                | 80      | Total power | 16 W   |

## Mounting mode

Wall mounted

## Shape and measurements

Length: 2.17 in

Width: 13.98 in

Height: 4.61 in

## Adjustability

Fixed

## Electric

System power: 16 W

## Protection

IP: 40

IK: 02